

The I-mode confinement regime on the ASDEX Upgrade tokamak: scrape-off layer properties and investigation of stationary and transient divertor heat loads

T. Happel,¹ P. Hennequin,² P. Manz,¹ F. Ryter,¹ D. Brida,¹ M. Dunne,¹ T. Eich,¹ M. Faitsch,¹ S. J. Freethy,^{1,3} L. Gil,⁴ L. Guimaraes,⁴ A. Merle,⁵ D. Nille,¹ J. Pinzón,^{1,6} D. Prisiazhniuk,¹ B. Sieglin,¹ U. Stroth,^{1,6} H. J. Sun,¹ E. Viezzer,⁷ and the ASDEX Upgrade¹ and EUROfusion MST1⁸ teams

¹Max-Planck-Institut für Plasmaphysik, Boltzmannstr. 2, 85748 Garching, Germany

²Laboratoire de Physique des Plasmas, Ecole Polytechnique, 91128 Palaiseau, France

³Plasma Science and Fusion Center, Massachusetts Institute of Technology, Cambridge, Massachusetts 02139, USA

⁴Instituto de Plasmas e Fusão Nuclear, Instituto Superior Técnico, Universidade de Lisboa, Portugal

⁵Ecole Polytechnique Fédérale de Lausanne (EPFL), Swiss Plasma Center (SPC), CH-1015 Lausanne, Switzerland

⁶Physik-Department E28, Technische Universität München, James-Frank-Str. 1, 85748 Garching, Germany

⁷Dept. of Atomic, Molecular and Nuclear Physics, University of Seville, Seville, Spain

⁸see the author list "H. Meyer *et al.*, Nucl. Fusion **57**, 102014 (2017)"

The I-mode is an improved confinement regime of tokamak plasmas where an edge transport barrier is observed only in the heat transport but not in the particle transport. This is in contrast to H-mode confinement, which is characterized by transport barriers for both heat and particles. The I-mode does not exhibit any ELMs. Since the particle confinement is low, the I-mode does not suffer from high impurity content and no impurity accumulation is observed. It is characterized by an instability called the weakly coherent mode (WCM) which resides at the plasma edge. After substantial I-mode research by the fusion community in the last years, the mechanism which creates a transport barrier in only one of the transport channels is still not understood.

An overview of recent I-mode studies on ASDEX Upgrade is given, including L-I and I-H power thresholds, pedestal and confinement properties [1], extending previous studies to higher Greenwald fractions up to 0.7. The confinement improvement in I-mode is accompanied by a deepening of the edge radial electric field well and a reduction of turbulence with respect to L-mode [1, 2]. A striking feature of I-mode edge turbulence is a reduction of low-amplitude density fluctuations, concomitant with the appearance of strongly intermittent high-amplitude density bursts in the plasma edge inside the separatrix [3]. These density turbulence bursts are linked to the WCM. After their generation, they are expelled from the plasma and appear later in the divertor, observed by bolometry, infrared thermography and Langmuir probes. The importance of these bursts in terms of transient divertor heat loads is assessed.

Moreover, stationary I-modes have been obtained recently with neutral beam injection heating. The stationarity allows the characterization of scrape-off layer (SOL) fall-off lengths of density and temperature. While the former are similar to L-mode plasmas, the latter are comparable to H-mode plasmas, indicating that I-mode properties are also found in the SOL. Infrared thermography data yields information on the scrape-off layer power fall-off length and divertor loads, and implications for future devices are discussed.

[1] T. Happel *et al.*, Plasma Phys. Control. Fusion **59**, 014004 (2017).

[2] F. Ryter *et al.*, Nucl. Fusion **57**, 016004 (2017).

[3] T. Happel *et al.*, Nucl. Fusion **56**, 064004 (2016).